

## **SOLVENT – 95 TYPE II**

**(ALIPHATIC NAPHTHA)**  
**TT-N-95B TYPE II**

### **Description**

**SOLVENT-95 TYPE II** (aliphatic naphtha) is intended for use for cleaning acrylic plastics. The product can also be used in the manufacture of organic coatings but usage is not limited to such applications.

In addition it may be used for electric motors, electric equipment, panel boards, pumps, valves, machinery, starters, generators, connectors, fans and blowers, cables and wires, distributors, military aircraft, mechanical parts, motors, engines, etc.

### **Advantages**

- Non-toxic
- It can be recycled
- Practically odorless
- Safe to all metals
- High cleaning ability
- Safe to the ozone layer
- Evaporates quickly and completely leaving no residues

### **Disadvantages**

- Very flammable (flash point approximately  $\ll -5^{\circ}\text{C}$ ).

### **Specifications**

**TT – N – 95B TYPE II.**

### **Usage**

**SOLVENT-95 TYPE II** is used neat and may be applied by brushing dipping or non-atomizing spray. Allow **SOLVENT-95 TYPE II** to completely evaporate leaving surface dry. When applied by immersion tanks should be covered with a lid to minimize evaporation of solvent.

### **Physical & Chemical Properties**

Appearance: Clear liquid

Specific gravity:  $0,72 \pm 0,01$

Flash point:  $< -5^{\circ}\text{C}$

Aromatic contents:  $< 0.01\%$

Evaporation rate: 4,5 (butyl acetate = 1)

### **Caution**

Avoid contact with skin and eyes. For further information refer to M.S.D.S.